



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 0 765 843 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication: 02.04.1997 Bulletin 1997/14  
(51) Int. Cl.<sup>6</sup>: C02F 1/467, C02F 1/48, A61L 9/22, C12N 1/06  
(21) Application number: 95309545.2  
(22) Date of filing: 29.12.1995

<p>(84) Designated Contracting States: AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL PT SE Designated Extension States: LT LV SI</p> <p>(30) Priority: 28.09.1995 JP 251623/95</p> <p>(71) Applicants: • Remodeling 21 Co., Ltd. Toshima-ku, Tokyo (JP) • Yoshida, Kanji Kumamoto-shi, Kumamoto-ken (JP)</p>	<p>(72) Inventors: • Yoshida, Kanji Kumamoto-shi, Kumamoto-ken (JP) • Sumioka, Teruaki Kumamoto-shi, Kumamoto-ken (JP) • Xu, Haitao Urawa-shi, Saitama-ken (JP)</p> <p>(74) Representative: Perry, Robert Edward GILL JENNINGS &amp; EVERY Broadgate House 7 Eldon Street London EC2M 7LH (GB)</p>
---	--

(54) **Deactivating or destroying microorganisms by an electrical charge**

(57) Applying electrical energy to a microorganism through a liquid, gas or solid having electrical energy causes an increase in an electric charge in excess of the limit of intracellular and extracellular electrostatic capacity possessed by the microorganism, which results in an irreversible change in the microorganism cells and/or explosively destroys the border membrane of the microorganism cells.

EP 0 765 843 A1

**BEST AVAILABLE COPY**

## Description

### Field of the Invention

The present invention relates to a process for deactivating or destroying microorganisms, for the purpose of bacteriolysis, virolysis, disinfection or sterilization.

### Background of the Invention

Various processes have been developed and proposed to perform bacteriolysis, disinfection and sterilization by efficiently destroying microorganisms including bacteria such as *Pseudomonas aeruginosa* and *Escherichia coli* and other *Eumycetes*, and minute viruses. However, none of these known processes has adequately considered the properties of microorganisms. For example, electrochemical sterilization is premised on bringing the microorganisms into contact with an electrode surface or dielectric substance, to inhibit their biochemical reactions. The surface of a bacterium typically has a negative charge and is attracted to a positive electrode, and is destroyed by contact. However, when the number of bacteria increases, they exhibit a state in which protoplasm accumulates inside the bacteria, that protects the bacteria with protein. They thus effectively have an electrical shield. This causes a decrease in bactericidal function which makes maintenance and management of the electrodes susceptible to the occurrence of problems. As a result, practical application is correspondingly difficult.

### Summary of the Invention

This invention is based on a consideration of the mechanism by which microorganisms are destroyed. It has been found that, when bacteria are destroyed, they emit cytoplasm prior to contact with a positive electrode. Bacteria can be considered to be microcapacitors; their cell membrane is destroyed when they are subjected to an electric charge in an electric field, and that charge exceeds the electrostatic capacity.

A process for deactivating or destroying microorganisms, according to the present invention, involves applying electrical energy to microorganisms, in a charged medium (liquid, gas or solid). One aim is to increase the electrical charge in excess of the limit of intracellular and extracellular electrostatic capacity possessed by the microorganisms, and/or to promote intracellular and extracellular osmosis of the microorganisms. Another aim is to cause an irreversible change in the microorganism cells, or to explosively destroy the cell membrane.

The present invention thus offers the advantage of giving extremely high bactericidal, viricidal, disinfection and sterilization effects. Since any liquid, gas or solid can be used to apply electrical energy to microorganisms provided that it is effectively electrically-energised, the present invention offers the advantage of selecting

from a very broad range of means for applying electrical energy, depending on the location where the microorganisms which are to be deactivated or destroyed are suspended or otherwise present.

### Description of the Invention

The medium in which the microorganisms are treated is preferably charged water. Electrical energy is applied after placing microorganisms in this charged water. Such charged water may be, for example, any of charging water, battery water, functional water, electrolysis treatment water, high oxidation potential water, strongly acidic electrolytic regeneration aqueous solution, ionized water, non-ionized water and electrified water. Alternatively, the medium may be a gas having an electric charge, or a solid charge-accumulating substance.

One or more electrodes may also be used. The process in this case comprises applying current to a liquid containing the microorganisms via an electrode and applying electrical energy. The microorganisms are in a non-contact state with respect to the electrode. A specific non-contact process, for purifying water, and apparatus for use therein, are described and claimed in a copending Patent Application filed in the same names and on the same date, entitled "Water Purification Process and Apparatus". Alternatively, current supplied via the electrode may also be applied via an electrical medium or non-electrical medium.

In this specification, the term "microorganism" is used in the generic sense to refer to bacteria, including *Eumycetes* and minute viruses. The term "cell membrane" is used in the broad sense, and refers generically to the boundary membrane, external membrane, interfacial membrane, protoplasmic membrane or cell wall that separates the protoplasm of the cell from the outside.

The term "explosively destroying" as used herein refers directly to the states where strong membrane contraction occurs, the cell membrane having high strong elasticity, such that the cell contents (protoplasm) spray out and scatter radially in all directions; where the cell membrane has low elasticity and the internal pressure of the cell is high, such that local destruction of the cell membrane occurs, causing translational spraying with little peripheral scattering; or where the cell membrane has weak elasticity and external pressure is relatively low, such that translational spraying and peripheral scattering occur. The same term is also used in the broad sense, to refer generically to destruction, including turgor pressure destruction as well as lysis, dehydration, coagulation, melting, perforation and so forth, which are typical phenomena of bacterial destruction.

The term "charged water" is used herein to refer generically to charging water, battery water, functional water, electrolysis treatment water, high oxidation potential water, strongly acidic electrolytic regeneration

aqueous solution, ionized water, non-ionized water or electrified water. The phrase "applying current" is not limited to the application of current via a conductive medium, e.g. a solution of a conductive substance such as NaCl, but also includes the application of current via a liquid that is not generally supposed to be conductive, such as purified water. It has been confirmed that when current is applied after viable microorganisms are suspended in purified water, a current is obtained that is smaller than that in a conductive medium. This is apparently the result of a jumping conductivity effect (a type of non-conductive medium current flow) that exists between microorganisms, by which microorganisms form a constant flow in the direction of the positive electrode.

The term "osmosis" refers to the phenomenon of water in solution moving towards the higher concentration side when divided by a water-permeable solute-impermeable membrane. If the osmotic pressure is increased, it causes destruction of the cell membrane. The term "irreversible change" is used to refer generically to states in which the cell membrane inhibits the transport of substances, the cell membrane itself is changed or modified, or the protoplasm is changed or modified.

The following Examples illustrate the invention. In each, five microorganisms, i.e. *Staphylococcus aureus*, *Escherichia coli*, *Pseudomonas aeruginosa*, *Candida* and influenza virus, were tested.

#### Example 1

Each of the five microorganisms was independently suspended in 0.01 ml purified water or tap water supplied by pipette, followed by dropwise addition of 0.01 ml drops of high oxidation potential water. The state of the microorganisms, in the form of a three-dimensional layer, was investigated using apparatus having a final maximum magnification factor of 4500X, consisting of an inverted system microscope IX-70 (manufactured by Olympus) equipped with a differential interference device and combined with a 355 mm (14 inch) monitor (with CCD). It was found that 70% of the microorganism cells ruptured and became debris after 1-drop addition, 80% after 2-drop addition and 99% after 3-drop addition, for all the five microorganisms listed above. Moreover, the amount of debris increased when 4 drops were added, and nearly 100% of the microorganism cells exhibited a state of destruction when the final, 5th drop was added.

*Pseudomonas aeruginosa* is considered to be more resistant than the other microorganisms. It is worth noting that the cells of this microorganism were destroyed in the same manner as the other microorganisms listed above. Although it was difficult to visually recognize destruction of the border of *Candida* cells since they inherently do not move, deactivation or destruction of *Candida* could be confirmed since the oscillation of nearly all microorganisms present had

stopped. In addition, during addition of the first three drops, some of the microorganisms had stopped moving but were not yet destroyed. In a very few cases, some microorganisms exhibited a slight degree of buoyancy.

#### Example 2

Each of the five microorganisms was independently suspended in 0.01 ml purified water and in 0.01 ml tap water. Electrical energy of 0.2-0.3 mA: 12 V and 0.5 mA: 12 V was applied to the purified water and to the tap water, respectively, via platinum electrodes. The cell membranes in 99% of the microorganisms were found to be ruptured.

#### Example 3

Each of the five microorganisms was independently suspended in 0.01 ml purified water. A discharge tube was brought near the preparations, and the ionized gas generated around the discharge tube was allowed to act on the preparations. It was found that the cell membranes in 99% of the microorganisms had ruptured. It was thus confirmed that the intended deactivation or destruction was effected without making contact with the microorganisms.

#### Example 4

Each of the five microorganisms was independently suspended in 0.01 ml purified water. A very small amount of carbon powder was sprinkled on the preparations. It was found that the cell membranes in 99% of the microorganisms had ruptured.

Similar results were obtained when electrostatically-charged polymer powder was used instead of the carbon powder. Further, when electrostatically-charged carbon powder was applied to dried microorganisms which can be wet-cultured, the degree to which those dried microorganisms could be cultured was extremely low.

#### Claims

1. A process for deactivating or destroying microorganisms, which comprises subjecting the microorganisms to an electric charge, in an electrically-energised liquid, gas or solid medium.
2. A process according to claim 1, wherein the charge is in excess of the limit of intracellular and extracellular electrostatic capacity possessed by the microorganisms.
3. A process according to claim 1 or claim 2, comprising promoting intracellular and extracellular osmosis of the microorganisms.

4. A process according to any of claims 1 to 3,  
wherein the medium is charged water.
5. A process according to claim 4, wherein the  
charged water is any of charging water, battery 5  
water, functional water, electrolysis treatment  
water, high oxidation potential water, strongly acidic  
electrolytic regeneration aqueous solution, ionized  
water, non-ionized water and electrified water. 10
6. A process according to any of claims 1 to 3,  
wherein the medium is an electrically-charged gas.
7. A process according to any of claims 1 to 3,  
wherein the medium is a solid charge-accumulating 15  
substance.
8. A process according to any of claims 1 to 3,  
wherein the medium is a liquid, and which com-  
prises applying a current to the liquid containing the 20  
microorganisms *via* an electrode that is not in con-  
tact with the microorganisms.
9. A process according to any of claims 1 to 8,  
wherein the medium is conductive. 25
10. A process according to any of claims 1 to 8,  
wherein the medium is non-conductive.

30

35

40

45

50

55



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 95 30 9545

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	WATER RESEARCH, vol. 24, no. 12, 1 December 1990, pages 1491-1496, XP000175524 PATERMARAKIS G ET AL: "DISINFECTION OF WATER BY ELECTROCHEMICAL TREATMENT" * page 1494, column 2, paragraph 2 * * page 1495, column 2, paragraph 2 * ---	1,4,5, 8-10	C02F1/467 C02F1/48 A61L9/22 C12N1/06
X	PATENT ABSTRACTS OF JAPAN vol. 94, no. 010 & JP-A-06 292891 (KENJI SHISHIDO), 21 October 1994, * abstract *	1,7,9	
X	PATENT ABSTRACTS OF JAPAN vol. 013, no. 179 (C-590), 26 April 1989 & JP-A-01 007964 (TOSHIBA CORP), 11 January 1989, * abstract *	1,6,10	
X	DE-A-32 33 282 (SCHMIDT BURBACH GERHARD PROF D;CASPER FRIEDHELM DR ING) 8 March 1984 * page 3, paragraph 1 - paragraph 3 * * page 5, paragraph 3; claims 1,2; figure 1 *	1,2,4,5, 9,10	TECHNICAL FIELDS SEARCHED (Int.Cl.6)  C02F C12N A61L
X	US-A-5 304 486 (CHANG DONALD C) 19 April 1994 * column 1, line 60 - column 2, line 5 * * column 2, line 50 - line 66 * * column 7, line 19 - line 45 * * column 8, line 3 - line 37 *	1-3	
X	US-A-5 048 404 (BUSHNELL ANDREW H ET AL) 17 September 1991 * column 2, line 41 - line 64 * --- -/--	1-3	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 14 January 1997	Examiner Ruppert, G
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 150 (01.92) (P/MCU)



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 95 30 9545

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	EP-A-0 468 478 (HOUSE FOOD INDUSTRIAL CO) 29 January 1992 * page 2, line 31 - line 41 * -----	1,8-10	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>14 January 1997</b>	Examiner <b>Ruppert, G</b>
<b>CATEGORY OF CITED DOCUMENTS</b> X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 150 (01.92) (P0401)

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**